# EPSON®
EXCEED YOUR VISION

# PowerLite® L260F 1080p 3LCD Lamp-Free Laser Display with Built-In Wireless

## Keep students engaged wherever they are in the classroom with bright, large images.

**Best-in-Class Color Brightness[1] with 3-chip 3LCD technology** — 4,600 lumens of color and white brightness[2]

**Incredible image quality** — High Definition 1080p resolution at an exceptional value; accepts 4K content

**No lamps to replace ever** — solid-state, 20,000-hour, virtually maintenance-free laser light source[3]

**Built-in wireless networking with enterprise-level security** — additionally, you can connect with Miracast®, which supports software-free, peer-to-peer wireless connectivity

**Connect and cast from up to 50 devices[4]** — free downloadable Epson iProjection™ software makes it easy to cast wirelessly from Chromebooks, iOS® and Android™ devices, Mac® computers and PCs[4]; with moderator feature[5], teachers never lose control of the displayed content

**Versatile display** — widescreen aspect ratio up to 16:6 and large image size up to 310" diagonal, with split screen[6] capability for side-by-side viewing

**Flexible installation** — 1.6x optical zoom, horizontal and vertical keystone, Quick Corner® and more makes upgrading from an old projector seamless

**Easily manage your fleet** — configure, monitor and control up to 2,000 networked projectors at once with the free downloadable Epson® Projector Management software[7]

**Create amazing effects and experiences** — built-in media player with Epson Projector Content Manager software[4] includes templates, effects, color filters and customizable options; playlist and playback functions allow for seamless content management for single or multiple PowerLite projectors

**Easily project wall-sized images** — built-in edge blending and split screen[6] features for easy, scalable projection

LASER
LIGHT SOURCE

3LCD

# PowerLite® L260F 1080p 3LCD Lamp-Free Laser Display with Built-In Wireless

## Specifications

**Projection System** RGB liquid crystal shutter projection system
**Driving Method** Poly-Silicon TFT Active Matrix
**Pixel Number** 2,073,600 dots (1920 x 1080) x 3
**Color Brightness[2]** Color Light Output: 4,600 lumens
**White Brightness[2]** White Light Output: 4,600 lumens
**Aspect Ratio** 16:9, Supports 4:3, 16:10, 16:9*, 16:6*, 21:9*
* With vertical image shift control within letterbox area.
**Light Source** Laser Diode
**Laser Light Source Life[3]**
Normal Mode: Up to 20,000 hours
Extended Mode: Up to 30,000 hours
**Throw Ratio Range** 1.32 – 2.12
**Size (Projected Distance)**
31'' - 310'' (0.88 m - 9.06 m)
**Keystone Correction (Manual)** Vertical: ±30 degrees; Horizontal: ±30 degrees
**Dynamic Contrast Ratio** Over 2,500,000:1
**Color Reproduction** Up to 1.07 billion colors

## Projection Lens

**Type** Optical zoom (Manual), Focus
**F-Number** 1.51 – 1.77
**Focal Length** 18.2 mm – 29.1 mm
**Zoom Ratio** 1.0 – 1.62

## Other

**Operating Temperature** 32 ˚F to 104 ˚F (0 ˚C to 40 ˚C) (low altitude: 0 ft – 7,500 ft), 32 ˚F to 95 ˚F (0 ˚C to 35 ˚C) (high altitude: 7,500 ft – 10,000 ft)
**Power Supply Voltage** 100 V – 240 V AC ±10%, 50/60 Hz
**Auto Power On** Signal Detection on HDMI®/Plug-In Detection (HDMI, USB, VGA 15-pin)
**Sleep Mode** Yes (with timer)
**Power Consumption**
Normal Mode: 272 W
Quiet Mode: 208 W
Standby Mode: 2.0 W
Energy-Saving Mode: 0.5 W
**Fan Noise**
Normal Mode: 37 dB
Quiet Mode: 27 dB
**Security** Enterprise Level Security Encryption

## Interfaces

1x D-Sub 15-Pin VGA Input
1x D-Sub 15-Pin VGA Input/Monitor Out
1x RCA Composite
2x HDMI (with CEC Control)
2x Audio In (3.5 mm stereo mini)
1x Audio In (Red/White RCA)
1x Audio Out (3.5 mm stereo mini)
1x D-Sub 9-Pin RS-232C
1x USB Type A (with 5 V/2 A power supply)
1x USB Type B (for copying setting)
1x Wired LAN RJ-45

Built-in wireless: 802.11 b/g/n (2.4 GHz) (DSSS/CCK, OFDM) 802.11 a/n/ac (5 GHz)* (OFDM)

## Dimensions (W x D x H)

**Projector (Including Feet)** 12.8" x 4.1" x 11.7"
**Weight** 9.5 lb

## Software

In addition to compatibility with Epson's standard suite of software, this product has a direct playback function via USB. Works with:
- Epson Projector Content Manager Software[7] (visit our support pages for the latest version)
- Epson Creative Projection application[7]

## Remote Control

**Features** Color Mode, A/V Mute, Focus, Zoom, Volume, Spotlight, HDMI, LAN, Keystone, Pattern, Menu, Effect, USB, Split, Computer, Freeze, Aspect, Home
**Operating Angle**
Front and Rear Remote Sensors
Up/down: -30 to +30 degrees
Right/left: -30 to +30 degrees
**Operating Distance** 20 ft (6 m)



* Maximum speed and range are achievable when used with same enhanced mode technology. Actual features and performance may vary depending on your computer system, the environment and other factors.

## Eco Features

RoHS compliant
Recyclable product[8]
Epson America, Inc. is a SmartWay® Transport Partner[9]

## Support

**Epson Connection℠**
Pre-sales support: U.S. and Canada (800) 463-7766
Website: www.epson.com
**Service Programs** 3-year projector limited warranty
Epson Road Service program, dedicated toll-free support (U.S. and Canada only)

## What's Included

PowerLite L260F standard-throw laser projector, projector remote control, two (2) AA batteries (for remote), HDMI cable, power cable, cable cover

## Ordering Information

| | |
|---|---|
| PowerLite L260F | V11HA69020 |
| Replacement Air Filter (ELPAF60) | V13H134A60 |
| Soft Carrying Case (ELPKS71) | V12H001K71 |
| Ceiling Mount (ELPMB60W) | V12H963210 |
| Wireless LAN Module (ELPAP11) | V12H005A02 |
| DC-07 Document Camera | V12H759020 |
| DC-13 Document Camera | V12H757020 |
| DC-21 Document Camera | V12H758020 |

1 Color brightness measured per IDMS 15.4. Additional colors and picture modes tested. Top-selling Epson 3LCD projectors vs. comparable top-selling 1-chip DLP projectors based on NPD sales data for October 2019 – September 2020. COLOR BRIGHTNESS WILL VARY BASED ON USAGE CONDITIONS. | 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 3 No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. | 4 For wireless functionality, including via the Epson iProjection App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection App does not support all files and formats. See www.epson.com for details. | 5 Moderator control, connecting via QR code and projector remote are not available on Epson iProjection for Chromebooks. | 6 Consult your user manual for Split Screen input combinations. | 7 Internet connection required for download. Data usage fee may apply. | 8 For convenient and reasonable recycling options, visit www.epson.com/recycle | 9 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

Learn more about how our products can empower your institution. Visit us at **www.epson.com/foreducation**

**Better Products for a Better Future™**
eco.epson.com

**SmartWay®**
Transport Partner
Getting There With Cleaner Air

**Contact:**

**Epson America, Inc.**
3131 Katella Ave., Los Alamitos, CA 90720

**Epson Canada Limited**
185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca