

CA1

70V INSTALLATION AMPLIFIER



Overview

The Coliseum CA1 public address amplifier has been designed specifically for installations where a versatile paging system with high quality music playback is required.

Ideal for restaurants, small clubs, offices and retail environments where a simple and reliable system capable of servicing multiple paging zones is required. Multiple inputs for microphone or source material, and voice activated paging from either a microphone or telephone matrix means the CA1 can be used in virtually any application.

Features

- 4-ohm speaker load, or four separate 70-volt speaker systems (one 'system' per zone)
- Delivers 180 watts (mono) @ 4 Ohms
- 6 Channels
- Phantom power included
- Zone Paging / Telephone interface built in
- 1/4-inch / XLR / RCA inputs
- Headphone monitor



Specifications

Amplifier class	70-volt
Power Output	180 Watts @ 4 Ohms 180 Watts @ 70-volts
THD - 1kHz (dB)	Less than 1%
Mixer - Signal to Noise Ratio (dB)	Greater than 55dB
Mixer Frequency Response (Hz, +/- 2dB)	50 - 15kHz
Cooling	Passive
Channels	6
Inputs	3 x 1/4" / XLR Combi-jack 2 x RCA Unbalanced
Outputs	Screw Terminals
Record Outputs	Yes
Tone controls	Bass & Treble
Controls	INPUT 1-4, AUX1-2 and tel. paging 1 master volume control 5 zone paging select switch
Phantom Power	Yes
Headphone Monitor	Yes - main Output
Rack Spaces	Two
Dimensions (DWH / D fm ears, inches)	13 x 19 x 6
Dimensions (DWH / D fm ears, cm)	32 x 48 x 15
Weight (lbs / kg)	24 / 9
Box Dimensions (LxWxH, inches)	22 x 16.5 x 9
Box Dimensions (LxWxH, cm)	56 x 42 x 23

Specifications subject to change without notice